

OIL & ENERGY CATALOG

9 11

VOLUME II

Table of Contents

Bonded Abrasives
Resin Bonded Abrasives
Coated Abrasives
Coated Flap Disc Abrasives
Wire Brush Abrasives
Cup Brushes
Scratch Brushes
Wheel Brushes
Adhesive Products
Adhesives & Glues
Putty
Sealing Products
Sealants
Tape Products
Duct Tapes
Electrical Tapes
Masking Tapes
Pipe Sealant Tapes
Cleaning Products
Cleaners & Degreasers
Insect & Weed Controlling Products 10
Insect Killers
Leak Detectors & Penetrants 10
Leak Detectors
Magnetic Particles
Penetrants
Lubricants & Penetrants 11
Anti-Seize Compounds
Fluids
Grease
Grease Guns
Multi-Purpose Lubricants
Oils
Coatings
Paint Brushes
Specialty Products 14
Finding Paste
Batteries 15
Flashlights & Lanterns 15
Strapping Products 15
Cable Ties
Tie Wire
Coolers & Chests 16
Chain, Cable, Rope & Accessories 17
Rope, Line & Twine
Straps & Bungee Cords
Derrick Tape Refills 17
Derrick Tapes
Gauging Tape Refills & Parts
Gauging Tape Wipers
Gauging Tapes
Plumb Bobs 19
Bending & Flaring Tools 19

Hand Benders
Clamps & Vises
Vises
Extractors & Sets
Extractor Sets
Files
File Sets
Half Round Files
Hammers, Sledges, Mallets & Axes
•
Hammers
Handsaws & Sets 21
Handsaws
Knives & Multi-Purpose Tools 21
Knives
Multi-Purpose Hand Tool Sets 21
Multi-Purpose Tool Sets
Pipe Threading Equipment 22
Threaders Manual
Threaders Manual Accessories
Threaders Powered
Threaders Powered Accessories
Pliers & Cutters
Cable & Wire Rope Cutters
Pipe Cutter Parts & Accessories
Tongue & Groove Pliers
Tubing Cutters
Prying Tools
Bars
Wrenches
Adjustable Wrenches
Pipe Wrench Parts & Accessories
Pipe Wrenches
Crayons
Markers
Covering Products
Plastic Sheeting
Tarps
Fittings & Accessories 27
Fittings
Tubing 27
Gage Glass
Babbit & Ladles 27
Coco Mats 27
Gage Poles
Packing Hooks
Rig Wash & Creme Beads 28
Safety Pins
Sample Bags
Sand Strainers
Spark Plugs
Compressors, Blow Guns, Hoses & Fittings 29
Air Hose Fittings
Cordless Tool Batteries & Chargers29

Batteries, Cordless Tool Drilling & Fastening Tools
Wrenches
Finishing Tools
Grinders
Pumping Equipment 32
Fuel Pumps
Clothing Protection
Coveralls & Overalls
Rainwear
Ear Protection
Earplugs
Eye Protection
Safety Glass Parts & Accessories
Safety Glasses
Fall Protection
Fall Protection Parts & Accessories
Fire, Gas & Water Protection
Detectors
Fire Extinguishers Hand Protection35
Gloves
Head/Face Protection
Faceshields & Visors
Hard Hat & Cap Parts & Accessories
Hard Hats & Caps
Escape Respirators
Respiratory Protection
Cartridge Respirators
Disposable Respirators
Torch & Weed Burners 37
Safety Storage 37
Safety Cans
Sweat Bands
Locking Devices
Padlocks & Cables
Heat Stress Protection 39
Activity Drinks
Spill Control Safety 40
Sorbents
Brushing & Sweeping Products40
Brushes & Brooms
Cleaning Products
Detergents Diskussking Classics
Dishwashing Cleaners
Disinfectants Floor & Carpet Cleaners
Personal Hygiene 41
Hand Cleaners
Wiping Products
Towels & Wipers
Waste Receptacles
Trash Can Liners





Honeywell Probrands



BONDED ABRASIVES

Resin Bonded Abrasives



Tiger[®] Pipeliner Grinding Wheels

Features:

- Designed specifically for pipeline applications.
- Whether grinding a bead, facing the land, prepping transitions, or fabricating in the yard, this 1/8 inch thick wheel (aka bead grinder, grinder disc) delivers aggressive
- grinding and reduced chatter throughout the life of the wheel.

Thickness: 1/8 in Arbor Size: 5/8 in

Grit: Z30T

Speed: 8500 RPM

SKU	Tool Shape	Dia.
804-58094	T27	7 in

COATED ABRASIVES

Coated Flap Disc Abrasives



Tiger[®] Disc Angled Style Flap Discs

Features:

Maximum aggression and long life.Smooth grinding action.

Smooth grinning action.
 Abrasive Material: Zirconium

Tool Shape: Type 29



SKU	Dia.	Grit	Speed
804-50519	4-1/2 in	60	13000 RPM
804-50520	4-1/2 in	80	13000 RPM
804-50544	7 in	60	8600 rpm

WIRE BRUSH ABRASIVES

Cup Brushes



Single Row Heavy-Duty Knot Wire Cup Brushes

Features:

- Knot wire cup brush provides heavy-duty, aggressive brushing action.
- Best suited for demanding cleaning applications on flat surfaces.
- Ideal tool for removing surface rust and light corrosion from bevel ends prior to welding.

Wire Size: 0.023 in

Arbor Size: 5/8 in - 11 UNC Wire Material: Steel

SKU	Dia.ww	Trim Length
804-12316	4 in	1-1/4 in
804-12276	5 in	1-3/8 in
804-12376	6 in	1-3/8 in

Scratch Brushes



Hand Scratch Brushes

Features:

- Heavy-duty industrial brushes.
- Wire fill and length is unsurpassed.
- Durable wood handle.
- Bristle Material: Carbon Steel

Block Material: Wood

Bristle Rows: 4 X 16



SKU	Handle Type	Handle Material
102-387	Shoe	Wood

Wheel Brushes

ANCHOR **Stringer Bead Wheel Brushes**

Features:

Dia.: 4 in



Face Width: 4 in Arbor Thread: 5/8 in - 11

Arbor Diam: 5/8 in - 11

No. of Knots: 30

SKU	Bristle Material	Bristle Diam
102-4\$58	Carbon Steel	0.02 in



Dually® Stringer Bead Wheels

Features:

- Up to the task for the most demanding multi-pass welding applications.
- Features a one-piece dual hex-nut that eliminates interference issues and simplifies periodic flipping of the wheel for maximum cutting action, longer life and safer use.

Steel

Dia.: 7 in

Arbor Diam: 5/8 in Face Width: 3/16 in Arbor Thread: 11 UNC

Bristle Mate SKU 804-79800

0.020 in

Roughneck[®] Max Stringer **Bead Wheels**

Features:

- Delivers unmatched weld cleaning performance by maximizing life, efficiency, and consistency.
- Improved feel and comfort during use makes brush operation effortless.
- Stronger, sharper wire delivers consistency and performance you can count on.
- Recommended for cleaning root pass welds, surface prep, and other cleaning applications.

Steel

Dia.: 4 in Arbor Diam: 5/8 in-11 UNC Face Width: 3/16 in

> **Bristle Materia** 804-13131



Bristle Diam

0.020 in



Roughneck® Stringer Bead Wheels

Features:

- Narrow face brush is suitable for cleaning root and hot passes.
- Effectively reaches into corners.
- Constructed from premium quality wire.
- Arbor Diam: 5/8 in
- Face Width: 3/16 in

Arbor Thread: 11 UNC

Bristle Material: Steel

SKU	Bristle Diam	Dia.	No. of Knots
804-13232	0.020 in	4-1/2 in	38
804-08756	0.020 in	5 in	38
804-09400	0.020 in	6 in	56
804-09000	0.020 in	7 in	56

ADHESIVE PRODUCTS

Adhesives & Glues



3M[™] Hi-Strength Spray Adhesive 90

Features:

- Has high-contact bond strength, one-minute dry time, high temperature resistance, low misting, precise spray control and variable width spray pattern.
- It can be used for decorative laminate bonding to tables or cabinets, shelving and bonding kick plates.

Adhesive Tensile Shear: 600 psi

Tensile Strength: 600 psi Chemical Compound: Acetone Working Time: 1 min to 10 min

> apacity Vo 405-021200-30023 17.6 oz





Brushable Ceramic


Features:

 When applied in a 15-20 mil coating, this low-viscosity, alumina-filled, brushable epoxy compound provides a smooth, protective barrier against wear, abrasion, corrosion, erosion, and chemical attack.



- Low-friction surface reduces turbulence, wear, and cavitations.
- Outstanding chemical resistance to acids, solvents, and alkalis.
- 3 colors (red blue white) to insure uniform coating.
- Red and white formulas are acceptable for use in meat and poultry plants.
- White is NSF-certified for use in potable water applications.
- 40-minute working time (Red,Blue).

 21-minute working time (White). Adhesive Tensile Shear: 2000 psi Tensile Strength: 3,800 psi Compressive Strength: 15,200 psi Chemical Compound: Epoxy Working Time: 40 min Dielectric Strength: 382 V/mil



Putty



Plastic Steel[®] Putty (A) Kits

Features:

- Metal-filled epoxy putty used for hundreds of routine maintenance, production, and tooling applications.
- Patch and repair areas where welding or brazing would be undesirable or impossible.
- Bonds to most metals, concrete, and some plastics.
- Cures at room temperature and forms a tough durable metallic mass that can be drilled, tapped, machined, or painted.
- Excellent resistance to oil, gasoline, water and many chemicals.

Specific Gravity: 2.8

Hardness: 85 Shore D

230-10110

Full Cure Time @ Temp.: 7 days @ 75° F

SEALING PRODUCTS

Sealants

GASOILA CHEMICAL

PLS[®] 2 Premium Thread & **Gasket Sealers**

- Features:
- Slow-drying, soft-setting, non-toxic, brushable, without grit.
- · Permeated with extra fillers to enhance sealing properties.
- Cures by solvent evaporation providing a durable, long-lasting seal that can be easily disassembled.
- Temp. Range: -100° F 600° F
- Weight .: 0.43 lb

SKU	Capacity Vol.
296-PB04	1/4 pt

LOCTITE

SI 596[™] High Temp Sealants

Features:

- Cures on exposure to moisture in the air to form a tough, flexible, waterproof, oil-resistant silicone rubber bond.
- This product resists aging, weathering and thermal cycling without hardening, shrinking or cracking.
- This product is also used as a sealant and adhesive for assembly and repair of industrial furnaces, ovens, boilers, exhaust stacks, high temperature ducting, and heating elements in electrical appliances.

Temp. Range: - 315° C

Full Cure Time @ Temp.: 24 hr

SKU	Capacity Vol.
442-2700556	190 mL



Temp. Range Dry 250° F; Wet 120° F



acity V

2 lb

LOCTITE.

Superflex[®] Red High Temp RTV Sealants

Features:

- Makes gaskets that resist temperatures to 600°F intermittent.
- Resists aging, weather, and thermal cycling without shrinking, cracking, or hardening.

Temp. Range: -75° F - 600° F

Full Cure Time @ Temp.: 24 h @ 77° F



SKU	Capacity Vol.	Packing Type
442-135507	80 mL	Tube
442-198817	300 mL	Cartridge

Thread Sealants with PTFE

Features:

- A general purpose sealant with the added lubricity of PTFE for metal pipes.
- Won't shred like tape and allows easy disassembly.

Temp. Range: -65° F - 300° F



5KU 442-1527514 Capacity Vol. 1 pt

Permate)

Capacity Vol

3.35 oz



Ultra Red[®] RTV Silicone Gasket Makers

Features:

- High temperature performance.
- Sensor-safe, non-corrosive, RTV silicone.
- Replaces almost any cut gasket.

Temp. Range: -65° F - 650° F

Full Cure Time @ Temp.: 7 days @77° F

230-81630



No. 5[®] Pipe Thread Sealants

Features:

- Soft-set, slow drying compound which seals, lubricates and protects threaded pipe and fittings.
- Ideal for application with a wide variety of fluids and gases, including potable water application.
- Use on threaded galvanized steel, iron, brass, copper, aluminum, stainless steel, polyethylene, reinforced fiberglass, PVC and CPVC pipes.

Temp. Range: -15° F - 400° F

Full Cure Time @ Temp.: 24 h @ 77° F

SKU	Capacity Vol.
622-25431	1 pt

Tru-Blu[™] Pipe Thread Sealants

Features:

- For refrigeration and industrial applications.
- Recommended for use on galvanized steel, iron, brass, copper, aluminum, stainless steel, polyethylene, fiberglass reinforced, PVC and CPVC pipe.
- Ideal for use as positive lock and seal on threaded fasteners.

Temp. Range: -50° F - 350° F

Full Cure Time @ Temp.: 24 h @ 77° F

SKU	Capacity Vol.
622-31431	1 pt







100% Silicone Architectural Grade RTV Sealants

Features:

- Superior quality, multi-purpose sealant provides a long-lasting, weather-resistant seal to glass, metal, plastic and ceramic surfaces.
- Offers excellent adhesion, flexibility, and durability without cracking, shrinking, or peeling.
- Can be applied at temperatures below freezing.

Temp. Range: -60° F - 400° F

Full Cure Time @ Temp.: 24 h @ 77 °F



TAPE PRODUCTS

Duct Tapes



3M[™] All Purpose Duct Tape DT8

Features:

- Instant adhesion to a wide variety of surfaces, including metal, glass, plastic and sealed concrete, by an aggressive natural rubber adhesive.
- Woven cloth scrim allows tape to tear easily by hand.
- Conformable backing is good for use on contoured surfaces.
- Good tensile strength for light duty bundling, repair, and holding.
 Thickness: 8 mil

Temp. Range: 150° F

Adhesion to Steel: 74 oz/in Tensile Strength: 31 lb·in

SKU	Length	Width
405-689330-17225	60 yd	1.88 in
	66 Ju	1.66 11

Electrical Tapes

3M

3M[™] Scotchrap[™] Vinyl Corrosion Protection Tape 50

Features:

G RDI

> Scotchrap[®] 50 and 51 tapes are tough, polyvinyl chloride based tapes with special high tack adhesive.



Formulated to resist corrosion
of metal piping systems above and below ground, fittings and
joints on all mill-coated pipe and electrical conduit systems.

Material: PVC

Thickness: 10 mil

SKU	Length	Width
500-106388	100 ft	2 in
500-106463	100 ft	4 in
000 100 100		



General Purpose Vinyl Electrical Tapes

Features:

- Excellent adhesion and elongation properties.
- General purpose electrical tape for household and industrial applications.

Material: PVC; Vinyl Thickness: 7 mil





© 2024



Super 33+[™] Vinyl Electrical Tapes

Features:

• Premium grade tape that provides electrical insulation for all wires and cables rated up to 600 V.



- Designed for above/below grade, indoor/outdoor, low and high voltage applications, and for harnessing cables.
- Offers electrical and mechanical protection with the combination of a pressure sensitive, rubber resin adhesive and elastic, PVC backing.
- Provides a protective jacket for high voltage cable splices.
- Highly resistant to UV rays, abrasion, moisture, alkalis, solvents, and many acids.
- Compatible with solid dielectric cable insulation, synthetic cable insulations, jackets, and splicing compounds.

Material: Rubber-Based Adhesive; Vinyl (PVC) Backing Thickness: 7 mil

SKU	Length	Width
405-638060-29035	76 ft	3/4 in

Masking Tapes



3M[™] General Use Masking Tape 201

Features:

- Proprietary, solvent-free adhesive formula removes cleanly in one piece with no adhesive residue.
- Sticks with confidence on wood, plastic, glass, metal and painted surfaces.

Roll Length: 55 m (60.14 yd) Thickness: 4.4 mil

metui			
5.			
14 yd)			

SKU	Length	Width
405-051115-64742	55 m	48 mm

ANCHOR

White PTFE Thread Sealant Tapes

Features:

- Tapes can be used in a wide variety of applications, from general purpose service such as water and air, to difficult service such as acids and pure oxygen.
- Easy installation, several wraps around the male threads and you're done.
- Made of 100% PTFE; compatible with almost any process fluid (except molten alkalis and elemental fluorine).
- Unlimited shelf life, no age deterioration, non-hardening. **Thickness**: 0.0035 in

SKU	Length	Width
102-1/2X520PTFE	520 in	1/2 in
102-3/4X520PTFE	520 in	3/4 in
102-1X520PTFE	520 in	1 in
102-1X1296PTFE	1296 in	1 in

Pipe Sealant Tapes

CLEANING PRODUCTS

Cleaners & Degreasers

Taus CHAMINGUA

B-12 CHEMTOOL[®] Carburetor/ Choke Cleaners

Features:

- Cleans petroleum residue from fuel systems, fuel injectors, valves, rings and pistons.
- Also works to disperse moisture.
- Great for use on oil returns, lifters, PCV valves, and oil pump screens.
- Utilizes High Energy Solvent Technology.
- Regular use ensures higher compression, fewer repairs, lower operation costs and increased spark plug and injector life.

SKU	Capacity Vol.
084-0117	16 oz





B-12

HEMTO

RBURE

CHOK

CLEANE



Brake Cleaners

Features:

- Effectively removes brake fluid, grease, oil and other contaminants from all brake parts.
- Cleans brake linings, disc brake pads, drums, cylinders, springs, and other related brake parts.
- Non-flammable, quick drying formula leaves no residue.

Chemical Compound: Methylene Chloride; Perchloroethylene; Toluene

> SKU 084-1420

apacity Vo 19 oz



Brake Parts Cleaners

- Features:
- Maintaining clean brake and disc parts can improve the life of your car's braking system and keep you safe on the roads.
- Using a brake cleaner for cleaning and degreasing is a great way to maximize the performance and increase the longevity of your entire brake system.

 Formulated to quickly and effectively remove grease, brake dust, brake fluids, oils, and other contaminants from brake parts, lining, pads.

 Options available for chlorinated and non-chlorinated formulas, including non-chlorinated that is less than 45% VOC (05084), ultra low VOC that complies with SCAQMD Rule 1171 (05151), and compliant with VOC regulations for all 50 states (05050).

SKU	Capacity Vol.
125-05084	14 oz
125-05050	20 oz
125-05089	20 oz



Heavy Duty Degreasers

Features:

- Effectively removes grease, oil, tar, and more to increase operating efficiency of equipment.
- Evaporates quickly.
- Leaves no residue and has no flash or fire point, making it an excellent alternative to 1,1,1-based cleaners.
- Use caution on plastics.

Chemical Compound: Chlorinated Solvent

SKU	Capacity Vol.
125-03095	20 oz

Lectra Clean[®] Heavy Duty Electrical Parts Degreasers

Features:

- Effectively removes contaminants to increase operating efficiency of energized electrical equipment.
- Evaporates quickly, leaves no residue and has no flash or fire point.
- Designed and labeled to be used on equipment where energy and/or residual exists during cleaning.

Chemical Compound: Chlorinated; Solvent

SKU	Capacity Vol.
125-02018	20 oz



simple green

Industrial Cleaners and Degreasers

Features:

- All-purpose cleaner, degreaser and deodorizer.
- Concentrate dilutes up to 1:30.
- Easily cuts through thick grease, oils, hydraulic fluids and built-up grime on all washable surfaces.
- Non-abrasive, non-corrosive, non-flammable and VOC compliant formula.
- Safe for use in cleaning equipment including floor scrubbers, carpet cleaners and parts washers.
- Orally non-toxic and readily biodegradable formula*.
- EPA Safer Choice product.
- Safer than caustic cleaners and solvents.

Chemical Compound: Ethoxylated Alcohol; Sodium Citrate; Sodium Carbonate; Citric Acid

SKU	Capacity Vol.
676-2710200613005	1 gal
676-2700000113008	55 gal

INSECT & WEED CONTROLLING PRODUCTS

Insect Killers



Wasp and Hornet Killer Plus[™] Insecticides

Features:

- Fast acting, high strength insecticide.
- Ergonomic trigger that provides control, even with gloved hands.
- Accurate up to 20 feet away.
- For any outdoor worker around electric and power utilities, telecommunications equipment and installation sites, bridge and tower maintenance, cable and wire installation sites, industrial plant grounds, warehouses, farm structures and buildings.

Insect Type: Crawling Bugs; Hornets; Wasps

SKU	Container Size	SKU
125-14010	20 oz	387-01-2250-78



LEAK DETECTORS & PENETRANTS

Leak Detectors

SNOOP

Leak Detectors

Features:

- Non-Toxic, non-flammable.
- Does not collect dust.
- Does not contain chlorine, aliphalic amines, or ammonium compounds.

Temp. Range: 27° F - 200° F

SKU	Capacity Vol.	Applications
747-80Z-SNOOP	8 oz	Gases

Magnetic Particles

MAGNAFLUX

Magnavis® 7HF Black Visible Magnetic Particle Wet Method Prepared Bath



Snoor

Features:

- Designed for spot inspections of parts that must be inspected in the field due to size or location.
- Composed of Magnavis[®]
 7C Magnaflux magnetic powder suspended in a low volatility mineral oil.
- Suitable for inspection of tubes, piping and other large structures.

SKU 387-01-1580-78

Magnavis[®] WCP-2 Contrast Paint

Features:

- Designed for use in applications where the contrast in color between the part being tested and the magnetic particles being used is insufficient for reliable identification of flaws.
- Composed of acetone and inorganic pigments and utilizes a carbon dioxide aerosol propellant for ease of application.
- Can be used with both dry and wet-method magnetic particles.





Penetrants



PB[™] Penetrating Catalysts

Features:

- Great for loosening rusted or frozen screws and bolts.
- Effective rust inhibitor.
- Non-evaporating lubricant.
- Penetrates into hard-to-reach areas.
- Suitable for brake, exhaust and suspension system jobs.
- Available with ProStraw[™] with Control Flow Technology[™] (16-PB-DS).



pacity Vo 11 oz

NETRA



Multi-Purpose Lubricants

Features:

- Lubricating ingredients are widely dispersed and hold firmly to all moving parts.
- Dissolves adhesives, allowing easy removal of labels, tape, stickers, and excess bonding material.



- Protects metal surfaces with corrosion-resistant ingredients to shield against moisture and other corrosive elements.
- Loosens rust-to-metal bonds and frees stuck, frozen or rusted metal parts.
- Product displaces moisture quickly and dries out electrical systems to eliminate moisture-induced short circuits.

Temp. Range: -50 °F - 300 °F

© 2024

SKU	Capacity Vol.
780-490040	11 oz
780-490057	12 oz
780-490088	16 oz
780-490118	l gal

LUBRICANTS & PENETRANTS

Anti-Seize Compounds

JET-LUBE

Kopr-Kote[®] High Temperature Anti-Seize and Lubricants

Features:

- Provides a shield against metal-to-metal contact, preventing seizure and corrosion.
- Assures protection against rust, oxidation, and corrosion.
- Specially formulated to prevent excessive over torque issues and has a very high static friction factor of 0.17.
- Unique blend of complex thickeners to help evenly distribute the copper flake onto the metal surfaces to eliminate metal to threaded metal contact.

Temp. Range: -65° F - 1,800° F Chemical Compound: Petroleum Based Thickener: Aluminum Complex Physical Form: Paste or Gel Flash Point: 430° F

SKU Capacity Vol. 399-10004 1 lb

LOCTITE.

LB 8008[™] C5-A[®] Copper Based Anti-Seize Lubricants

Features:

- Exclusive formula suspends copper and graphite in a high quality grease.
- Protects metal parts from rust, corrosion, galling, and seizing.
- Establishes greater clamp load.
- Known as Loctite[®] C5-A[®].

Temp. Range: -20 °F - 1800 °F

Chemical Compound: Petroleum; Mineral Oil; Calcium Dihydroxide; Copper; Graphite; Quartz

Physical Form: Paste

Flash Point: >199.4 °F

SKU	Capacity Vol.
442-160796	1 lb



UBRICANT

LOCT/17

LOCTITE.

Silver Grade Anti-Seize Lubricants

Features:

- Heavy duty, temperature resistant, petroleum-based lubricant compound fortified with graphite and metallic flake.
- Inert and will not evaporate or harden in extreme cold or heat.
- For use in assemblies.

NLGI Grade: 1

CHEMICALS, LUBRICANTS & PAINTS

Temp. Range: -15 °F - 1600 °F Chemical Compound: Graphite; Mineral Oil Physical Form: Paste Flash Point: >199.4 °F

SKU 442-199012

NEVER-SEEZ

Blue Moly Compounds

Features:

- Provides excellent protection against extreme pressure and high temperatures.
- Contains no graphite, lead or copper and can be used in applications where these are undesirable or prohibited.

Temp. Range: -150°F - 1500 °F Chemical Compound: Molybdenum Disulfide


Flash Point: 482 °F

SKU 535-30801134

Pure Nickel Special Compounds

Features:

- Excellent heat dispersing qualities.
- Prevents galling on steel-to-stainless, titanium, magnesium and other hard metals.



SKU	Capacity Vol.
535-30803818	8 oz
535-30801135	16 oz

NEVER-SEEZ

Regular Grade Compounds

Features:

- Protects against rust, corrosion, carbon fusion and seizure at high temperatures.
- Keeps parts working longer with less wear, and enables faster disassembly when repairs are needed.

Temp. Range: -297°F - 1800 °F Chemical Compound: Copper; Graphite;

Aluminum

Flash Point: 475 °F Capacity Wt.: 16 oz

SKU	Capacity Vol.
535-30803827	16 oz
535-30803817	16 oz

Fluids



EP-Xtra[®] Cutting Fluids

Features:

- Outstanding performance for any cutting operation on any metal.
- Absolutely without equal on hard metals and on cuts requiring extreme pressure or long cutting times.
- Metal cutting fluid used to increase speed, extend tool life and improve cut quality

SKU	Capacity Vol.
702-10016E	16 oz

CRC

Jump Start[®] Starting Fluids with Lubricity

Features:

- Re-start your engine in both cold and humid conditions.
- Specially formulated to work and withstand even the harshest winter weather, in freezing temperatures as low as -65° F.
- Can be used on diesel engines and gas engines, making it economical and versatile.
- Can also be used on other carburetor fuel systems as well, including snow blowers, lawn mowers, and motorcycles.
- Spray in air intake or air cleaner while engine is off.
- Lubricates upper cylinders.

SKU	Capacity Vol.
125-05671	11 wt oz









pacity Vo

NEVER-SEE

Nickel St


16 oz

pacity Vol

8 nz

CTITE

LB 8150



Coatings

Oils




Kroil Penetrating Oils

Features:

- Kroil guickly loosens rusted nuts and bolts, frees frozen shafts, pulleys, and more.
- Will not attack or damage metals.
- · Penetrates quicker and deeper than similar products.
- Use on any corroded threads or tight parts.
- Temp. Range: 122° F

Flash Point: 132° F





Marvel[®] Mystery Oil Gas and **Oil Additives**

Features:

- Engine and fuel additive helps prevent oil breakdown caused by extreme temperatures.
- Reduces and prevents valve-sticking by removing harmful sludge and carbon deposits.
- Added to fuel, it helps improve mileage by reducing deposits on injectors and carburetor jets.

Flash Point: 128° F

SKU	Capacity Vol.
465-013R	32 oz
465-MM085R1	32 oz
465-MM14R	128 oz

RIDGID

Thread Cutting Oils

Features:

- Cools threads and pipe during operation.
- Speeds metal removal.
- Improves thread quality.
- Reduces threading torque.
- Free of chlorine and other halogens, PCBs and heavy metals (complete MSDS available).

Flash Point: 385° F

632-70830



Capacity Vo

l gal



Protective Coatings

Features:

- Stirring thins to brushing, rolling or spraying consistency without the use of thinners.
- Excellent under severe corrosive conditions. Adaptable to underground and/
- or underwater installations. **Coverage** @ Vol.: 1091 sq ft @ 1 mil; 61 sq ft @ 18 mil

Temp. Range: 50° F - 110° F

Full Cure Time @ Temp.: 12 h @ 75° F; 24 h @ 50° F; 8 h @ 90° F

SKU	Capacity Vol.
107-50-1	l gal
107 00 1	. 8

Paint Brushes



White Chinese Bristle Paint **Brushes**

Features:

- Natural wood finish handle with White Chinese bristles.
- Steel ferrule.
- Perfect for latex paints, chip, and touch-ups.

Bristle Material: White Chinese

Handle Material: Wood

SI	KU	Brush Width	Thickness	Trim Length
449-1	500-3	3 in	3/8 in	1-1/2 in
449-1	500-4	4 in	5/8 in	2 in

SPECIALTY PRODUCTS

Finding Paste




Water Finding Pastes

Features:

- Golden brown turns red on contact.
- Gauges petroleums for water
 - content, sulphuric acid, nitric acid,


hydrochronic acid, ammonia, soap, salt, and other chloride solutions.

SKU	Capacity Vol.
460-KK01	3 oz



carboline

TUMASTIC® 50





BATTERIES

PROCELL

FLASHLIGHTS & LANTERNS

- between either a bright light
- 90 degree tilting head prevents neck fatigue.
- IPX4 rated for water resistance and 2 meter impact resistance tested.
- Includes batteries, elastic headstrap and rubber hard hat strap.

Lumens: 80

Lamp Life: 100000 h

Includes: Batteries; Elastic and Rubber Hard Hat Straps

SKU	No. of Batteries	Batt. Size
683-61050	3	AAA

ST	R	A	P	P	IN	G	Ρ	R	0	D	U	C 1	٢S

<u>Cable</u> Ties

ANCHO

General Purpose Cable Ties

Features:

- Nylon 6/6 features light weight, high strength and a wide temperature range.
- Even at higher than recommended temperatures or exposure to flame, nylon

does not give off toxic or irritating by-products.

Thickness: 0.054 in


Tensile Strength: 50 lb

SKU	Length	Width	Bundle Diam
102-1150N	11.1 in	0.18 in	3 in
102-1450N	14.6 in	0.18 in	4 in

DURACELL

Procell® Batteries

Features:



Recommended for scheduled battery replacement programs.

 Economically packaged in bulk and individually date-coded for effective inventory management.

Battery Type: Non-Rechargeable Dry Cell Alkaline

SKU	Batt. Size	Quantity
243-PC2400BKD	AAA	24 Batteries per Pack
243-PC1500BKD	AA	24 Batteries per Pack
243-PC1604BKD	9.0 V	12 Batteries per Pack
243-PC1400	С	12 Batteries per Pack
243-PC1300	D	12 Batteries per Pack

Procell® Intense **Batteries**

Features:

- Reliable performance.
- Excellent resistance to corrosion.
- Designed to meet all major quality, safety, and environmental standards.

Voltage: 1.5V DC

Battery Type: Alkaline

SKU	Batt. Size	Quantity
243-PX1500	AA	24 Batteries per Pack
243-PX2400	AAA	24 Batteries per Pack
243-PX1604	9V	12 Batteries per Pack
243-PX1400	С	12 Batteries per Pack
243-PX1300	D	12 Batteries per Pack



Trident® Headlamps

Features:

- Offers the versatility of switching to illuminate objects at a distance, or a soft flood light for tasks at arm's length.
- Push button switch is easy to use when wearing gloves.

Batt. Type: Alkaline

Modes: Xenon; 1 LED; 3 LEDs

Run Time: 150 h - 1 LED

SKU	No. of Batteries	Batt. Size
683-61050	3	AAA







UV Stabilized Cable Ties

Features:

FASTENERS, CLAMPS & STRAPS

- General purpose use.
- Nylon 6/6 features light weight, high strength and a wide temperature range.
- Contains increased resistance to UV light (does not totally eliminate the destructive effects of the light).

SKU	Length	Width	Bundle Diam
102-1150UVB	11.1 in	0.18 in	3 in
102-12120UVB	12 in	0.298 in	3 in
102-1450UVB	14.6 in	0.18 in	4 in
102-15120UVB	15 in	0.298 in	4 in
102-24175UVB	24.5 in	0.350 in	7.2 in

Gardner Bender

Heavy-Duty Cable Ties

Features:

- DoubleLock[™] design has teeth on both sides of the tie.
- Durable nylon construction.
- Great for bundling wire, cable, hose, ducts and countless other applications.

Thickness: 0.07 in

Tensile Strength: 175 lb

SKU	Length	Width
623-46-418UVB	18 in	0.35 in

Standard Cable Ties

Features:

- Patented DoubleLock design has teeth on both sides of the tie, ensuring 50% greater strength than industry standards.
- Made from durable 6/6 nylon material.Serviceable through
- temperatures of 32° 185° F.
- Great for bundling wire, cable, hose, ducts, and countless other applications.

Thickness: 0.055 in Tensile Strength: 75 lb Bundle Diam: 3 in

SKU	Length	
623-46-310UVB	11 in	



Tie Wire

IDEAL^{ix and} R<u>EEL</u>

Tie Wires

Features:

- These sturdy, versatile tie wires are efficient for indoor and outdoor jobs.
- Made of stainless steel or black annealed finish, the tie wires are essential for fastening items together.
- Wires have a high level of strength and are capable of handling heavy items.
- Wt.: 3-1/2 lb

SKU	Wire Size
132-71572	16 gauge

COOLERS & CHESTS



400 Series Coolers

Features:


- Ultratherm[®] insulation for maximum cold retention and maintains ice for up to 3 days in temperatures as high as 90°F.
- HDPE hide won't chip, peel, buckle, or rust.
- UV stabilizers prevent fading, cracking in all exposures.
- Front

push-button spigot is drip-resistant.

- White FDA Grade liner is easy-to-clean and resists stains and odors.
- Wide mouth pressure fit lid for easy filling.
- Keeper cord prevents lid loss.

SKU	Width	Length	Height
385-431	13-1/2 in	14 in	14 in
385-451	13 in	14-1/2 in	20.38 in
385-4101	15-7/8 in	23-1/4 in	23-1/4 in





IGLOO

Width 0.17 in

CHAIN, CABLE, ROPE & ACCESSORIES

Rope, Line & Twine



Manila Ropes



- Under normal service conditions,
- recommended working load of rope in good condition is 10% of the minimum breaking strength of new rope.
- A lower working load is recommended for critical applications.

SKU	Dia.	Length
103-1X100-3S	1 in	100 ft

ORION 🚆

Twisted Manila Ropes

Features:

- Natural fiber rope.
- Less strength than synthetic of equal diameter.
- Excellent rendering characteristics as needed in block and tackle work.

SKU	Length
811-330240-00100-60019	100 ft
811-330400-00100-60050	100 ft
811-330320-00600-60023	600 ft
811-330160-00600-60016	600 ft
811-330080-01200-60013	1200 ft



Spot Cord®

Features:

- High tenacity nylon core adds extra strength and reduces stretch.
- Coating provides chemical, weather and heat resistance.

Load Cap.: 1000 lb

Dia.	Length
1/4 in	100 ft





Tiger Sash Cord[™]

Features:

- Sleek and sturdy cord designed with a smooth, non-scoring surface for use with gaskets and packing.
- Solid braided cover with cotton core.
- Non-spliceable, for added strength.

Load Cap.: 450 lb

SKU	Dia.	Length
650-004020001060	5/16 in	100 ft

Straps & Bungee Cords

KEEPER 🔪

Ratchet Tie-Down

Straps

Features:

- Webbing is abrasion-resistant, won't rot or mildew, and maximizes strength.
- Ratchet provides greater tension with minimal force.
- Safety-first, spring-loaded release mechanism prevents ratchet from opening accidentally.

Length: 27 ft

Width: 2 in Load Cap.: 3,333 lb

SKU	End Type
130-04622	Double J-Hooks; Open Molded Handle; Steel Ratchet
130-04623	Flat Hooks; Open Molded Handle; Steel Ratchet

DERRICK TAPE REFILLS



Derrick Tape Refills

Features:

- Replacement blade for Derrick Chrome Clad[®] Tape.
- Durable steel construction.

Blade Style: ET

Blade Type: Chrome Clad®

For Model: C2276D

Wt.: 1.6 lb



SKU	Blade Length	Blade Width
182-0C2276DN	100 ft	1/4 in

DERRICK TAPES

CRESCENT Lufkin **Derrick Surveying** Tapes Features:



FASTENERS, CLAMPS & STRAPS

- Extra large winding drum provides rapid line recovery and permits tape line to be easily detached from reel.
- Special hook ring with ribbed face at zero.
- Leather thong is provided to use through eye at rear when tape is removed from reel.

Blade Thickness: 0.019 in

Increment @ Scale: 0.01 ft @ 1 ft

No. of Scales: 1

Blade Material: Steel

Blade Finish: Chrome Clad®

End Type: Hook w/Ring

SKU	Blade Length	Blade Width
182-C2276DN	100 ft	1/4 in

GAUGING TAPE REFILLS & PARTS

CRESCENT Lufkin

Oil Gauging Tape Replacement Blades

Features:

 Replacement measurement blade for oil gauging tape.

Durable finish.

Length: 25 ft Width: 1/2 in

Measuring System: SAE

SKU	Blade Style	
182-0CN1290SF590N	D1	
182-0C1290SF590N	D4	

GAUGING TAPE WIPERS

"LITTLE JOE"

Wipers

Features:

- Framework contructed of tough light weight die cast aluminum alloy.
- Stainless Steel screws, nuts, and heavy duty pin.



708-LITTLE-JOE

Body Materia Aluminum

GAUGING TAPES

CRESCENT Lufkin

Atlas[®] Oil Gauging Tapes

Features:

- Heavy-duty frame designed for years of rugged use.
- All frames include a grounding strap.
- Choose from Chrome Clad[®], Chrome Clad[®]/Nubian[®], or Nubian[®] styles.
- Plumb bob must be ordered separately.

Increment @ Scale: 1/8 in @ 1 ft

SKU	Blade Length	Blade Width	Blade Style
182-C1290SF590N	25 ft	1/2 in	D4
182-CN1290SF590N	25 ft	1/2 in	D1
182-CN1291SF590N	33 ft	1/2 in	D1

TAPE

Oil Tank Gauging Tapes

Features:

- Safety yellow handle with grounding wire.
- Large hub flange protects tape tail for Pop Out.
- New stronger core/handle interface has more threads per inch.
- Longer crank arm speeds retraction. Blade Style: Derrick


Increment @ Scale: 0.01 ft @ 1 ft

SKU	Blade Length	Blade Width
700-59625	100 ft	1/4 in





PLUMB BOBS



Benders

Features:

- Offset cushion grip handles eliminate knuckle cracking when forming 180° bends.
- A 90° start angle and unique oil absorbing
 - shoe minimize bending effort while forming accurate bends in copper, steel and stainless steel tubing.

Jaw Width: 1 in

Body Material: Steel

	SKU	Radius	Tube O.D.	Overall Length
ĺ	632-36097	15/16 in	3/8 in	13 in
ĺ	632-36132	1-1/2 in	1/2 in	17 in

CLAMPS & VISES

Vises



Top Screw Bench Chain Vises

Features:

- Rugged cast-iron base has handy pipe rest and bender.
- Crank handle is anchored to base.

Material: Cast Iron Base with

Anchored Crank Handle

SKU	Pipe Cap.
632-40195	1/8 in - 4 in
632-40210	1/4 in - 6 in

TRISTAND® Portable **Chain Vises**

Features:


- Optimized base for more working area.
- Benders are located at the rear of the base and three tool hangers are provided.

 - provides a conductive surface to connect the weld ground.
- Leg chain retains legs even when subjected to rugged use during operation and transport.
- Rugged tool tray offers prolonged stability before requiring a leg adjustment.

SKU	Pipe Cap.	Material
632-36273	1/8 in - 6 in	Ductile Iron Work Surface; Hardened Steel Jaws and Tubular Legs

EXTRACTORS & SETS

Extractor Sets



Half Round Files

CRESCENT NICHOLSON

Half-Round Files

Features:

- Used on concave, convex and flat surfaces.
- Rounded on one side, flat on opposite.
- Backs of all half-round bastard files are double-cut.
- Backs of all 4 in and 6 in files are single-cut.
- Backs of all half-round second-cut files are longer than 6 in are double-cut.

Tool Shape: Straight

Length: 14 in

SKU	Cut Type
183-05190N	Double-Cut Bastard
183-05194N	Double-Cut on Flat Side; Bastard Cut

HAMMERS, SLEDGES, MALLETS & AXES

Hammers



Bricklayer's Hammers

Features:

- Non-Sparking.
- Non-Magnetic.
- Corrosion resistant.
- Made in the USA.
- Beryllium-free.
- Handle Type: Straight

Handle Material: Fiberglass

Wt.: 1.9 lb

SKU	Head Weight	Overall Length
065-H-10FG	1-1/2 lb	14 in

TRUE TEMPER.
Sledge
Hammer Handles
Features: • Replacement sledge handle.
 Provides ergonomic hand comfort and absorbs shock.

- Durable hickory wood construction.
- Used With: 6 lb to 16 lb Sledge Hammer Head

SKU	Material
027-2036200	Hickory

Items in this catalog are a selection of our core offerings. Additional sizes, colors, flavors, and scents may be available for certain items. Visit our website for additional product information.

TRUE TEMPER.

Toughstrike American Hickory Engineer Hammers

Features:

- American hickory handle reduces shock.
- Double-face forged steel hammer head for maximum durability.
- Wedge/ring connection for trusted head retention.
- Used for heavy hammering, light demolition work, and driving spikes/wedges.

Handle Type: Wood Handle Length: 15 in Grip Style: Bare Wood

Handle Material: American Hickory

SKU	Head Weight
027-20184100	3 lb
027-20184200	3 lb
027-20184300	3 lb
027-20184600	4 lb

Toughstrike American Hickory Sledge Hammers

Features:

- American hickory handle reduces shock.
- Double-face forged steel hammer
- head for maximum durability.
- Overstrike protection to prevent handle breakage.
- Wedge/ring connection for trusted head retention.
- Used for heavy demolition work and driving spikes/wedges.

Handle Type: Wood

Handle Length: 36 in

Grip Style: Bare Wood

Handle Material: American Hickory

SKU	Head Weight
027-20185000	8 lb
027-20185200	10 lb
027-20185300	12 lb
027-20185400	12 lb
027-20185500	16 lb

HANDSAWS & SETS

Handsaws





lade Length

10-1/2 in

Heavy Duty Hacksaw Frames

Features:

- High impact, contoured handle.
- 45° blade adjustment.
- Throat Depth: 3-3/8 in

Handle Material: Molded Plastic

SKU 183-80952

KNIVES & MULTI-PURPOSE TOOLS

Knives

STANLEY

Self-Retracting Utility Knives

Features:

- Spring-loaded blade retracts into knife automatically when any second se
- when pressure on slide button is released.
- Knife can't be left around or put in a pocket with the blade exposed.
- INTERLOCK[®] nose secures blade safely between knife halves.

Blade Length: 2-1/8 in Blade Style: Self-Retracting Blade Tip Shape: Round Point Includes: (1) 11-987 Blade Height: 3/4 in Width: 1-5/16 in

SKU	Handle Length	Overall Length
680-10-189C	5-7/8 in	5-7/8 in
	· · · · · · · · · · · · · · · · · · ·	

MULTI-PURPOSE HAND TOOL SETS

Multi-Purpose Tool Sets

CRESCENT

1/4 in and 3/8 in Drive 6-Pt SAE/Metric Professional Tool Sets



Features:

- Contains a carefully selected assortment of hand tools needed for most industrial, mechanical, and consumer applications.
- Incredible access from long wrenches with narrow heads, adjustable wrenches and pliers, and a long-beam ratchets with small teardrop heads.
- Long nose and diagonal pliers with professional, ergonomic dipped grips wipe clean easily.
- Co-molded bit driver and screwdriver handles with ergonomic grip for improved performance.
- Shallow and deep SAE/metric 6-point full polish chrome sockets with stamped size markings for easy socket identification.
- 6 inch adjustable wrench with hex jaw design reduces slippage by gripping fasteners tightly.
- Manufactured from chrome alloy steel for better strength and longer tool life.
- Includes blow mold case for storage and organization.
- Quantity: 180 Pieces per Set

Includes: (2) Ratchets; (3) Extensions Adapter; (51) Standard Sockets; (31) Deep Sockets Spark Plug Socket; (12) Combination Wrenches; (24) Hex Keys; (2) Pliers Adjustable Wrench; (4) Screwdrivers Magnetic Bit Driver; (46) Bits; Bit Adapter

181-CTK180 1/4 in; 3/8 in	

PIPE THREADING EQUIPMENT

Threaders Manual

RIDGIL

Exposed Ratchet Threader Sets

Features:

HAND TOOLS

- All threader sets use same 12-R dies in die head.
- All matched threader/sets include die heads, ratchet assembly, ratchet handle and alloy dies.

SKU	Pipe Cap.	Includes
632-36475	1/2 in (NPT) - 2 in (NPT)	12-R; Alloy Dies; Die Heads; Ratchet Assembly

Threaders Manual Accessories

RIDGIL

Manual Threading/Pipe and Bolt Dies Only

Features:

- Professional-grade cutting tool.
- Precision threading.

Used With: 12-R

Wt.: 0.46 lb

SKU	Thread - TPI or Pitch	Cutting Direction
632-37895	2 in - 11-1/2 NPT	Right

RIDGID

Model 300 Power Drive **Threading Machines**

Features:

- Cam-action rear centering device turns with chuck.
- Two heavy-duty support bars.
- Speed grip chuck with
- replaceable jaw inserts.
- Forward/Off/Reverse switch and integral On/Off foot switch.
- Lightweight, portable design.
- Self-contained oil system with adjustable flow control.
- Ideal for use with RIDGID[®] roll groovers.
- Convert to portable threading machine with Model 141, 2-1/2 inch to 4 inch (36620), and Model 161, 4 inch to 6 inch (36630), both Sold Separately.
- Choose from 300 Power Drive Complete (15682 and 15722) or 300 Power Drive Only (41855 and 75075). Speed: 36 RPM

Amps: 15 A

Power Cap.: 1/2 hp

Phase: Single

Includes: (1) 300PD, Tool Only, 115V 25-60Hz 38 RPM NPT (41855); ; (1) 300PD Clip-On Tool Tray (22638); (1) 811A 1/8 in to 2 in NPT Die Head, Self-Opening, RH (97065); (1) 1/2 in to 3/4 in Universal Alloy Die Set (47745); (1) 1 in to 2 in Universal Alloy Die Set (47750); (1) 360 Cutter Assy (42370); (1) 311 Carriage with Lever (68815); (1) #32 Transport Cart (42575); (1) 341 Reamer Assy (42365); (1) 1206 Stand (42360); (1) Oiler with One Gallon Premium Thread Cutting Oil (10883)

SKU	Pipe Cap.	Voltage
632-15682	1/8 in - 2 in	115 V AC

Model 700 Power Drive/Hand **Held Threaders**


Features:

- Heavy-duty hand-held power drive.
- Designed for RIDGID[®] Model 12-R die heads. Other RIDGID[®] die heads (OO-R, OO-RB,
- 11-R) can be used using adapters.
- It can also be used with 258/258XL pipe cutters.
- Double-throw reversible switch.
- Spur gear reduction face gear drive, spring-loaded adapter pawls, and hardened steel spindle gear.
- Cast aluminum body.
- Speed: 36 RPM
- Amps: 13 A
- Power Cap.: 1/2 hp


Phase: Single Phase; Universal

Includes: 700 Power Drive; Die Head/Dies Sold Separately

SKU	Pipe Cap.	Voltage	
632-41935	1/8 in - 2 in	115 V	









Threaders Powered Accessories

RIDGID

Manual Receding Threader Pipe Dies

Features:

- High speed.
- Replacement pipe dies.
 Thread Size: 1 in thru 2 in-11-1/2 NPT
 Used With: Models 65R-C/65R-TC
 Ratchet Threaders



SKU 632-38100

Oilers

Features:

- An ergonomic 2-finger trigger design that reduces user fatigue.
- Twist and lock drip pan that easily locks in place.

 Die cast heavy duty body
 Used With: Manual Threading, 300 PD

> SKU 632-10883

Container Size 1 gal

RIDGID

Pipe Dies for Machine Die Heads

Features:

- Strong and durable pipe dies for use in universal die heads.
- Applicable to a wide variety of die heads.
- A convenient replacement to keep systems functioning for longer.

Pipe Cap.: 1 in - 2 in

SKU	For Model
632-47770	Universal Die Heads Nos 504A/711/713/811A/81 5A/816/817/842

RIDGID

Power Threading Die Heads for 2 in Threading Machines

Features:

- All die heads are through-head oiling.
- No 500A Die Head replaces the No 500 Mono Die Heads.
- Individual machine die heads do not include dies.

Pipe Cap.: 1/8 in - 2 in

Used With: Compact Threading Machine; Power Threading Machine

SKU	For Model
632-97065	1215, 1233, 535, 535A, 300 Compact Machines and 300 Power Drive

V-Head Pipe Stands

Features:

- V Head pipe stand.
- Locking ring allows for quick vertical height adjustments.
- Durable steel construction.
 Height Adjustment: 28 in 53 in

Pipe Cap.: Up to 12 in

Wt. Cap.: 2500 lb

Used With: Roll Groovers; Threading Machines

5KU 632-56662

PLIERS & CUTTERS

Cable & Wire Rope Cutters

Wire Rope Cutters

Features:

- Portable impact cutter, actuated by striking with a hammer.
- These cutters are precision engineered to deliver a cut without affecting the original roundness of the wire rope.
- Cut Type: Shear Cut
- Jaw Material: Heat-Treated Tool Steel Handle Type: Plunger

SKU	Cable/Wire Size
505-101	3/4 in Wire Rope
505-131	1-1/2 in Wire Rope





Pipe Cutter Parts & Accessories

RIDGID

Pipe Cutter Replacement Wheels



Features:

- These wheels are
 - precision-machined from high-grade steel.
- Engineered for long life and maximum cutting accuracy.

Applicable Materials: Steel/Ductile Iron

SKU	For Model
632-33105	1A; 202; 2A; 360; 42A; 732; 820/364
632-33125	44S; 466C; 466S; 468S; 764

Tongue & Groove Pliers

CHAN NEL LOCK

Tongue and Groove Pliers

Features:

- CHANNELLOCK BLUE[®] grips for comfort.
- Undercut tongue and groove design won't slip.
- Patented reinforcing edge minimizes stress breakage.
- PermaLock[®] fastener eliminates nut and bolt failure.
- Choose from a variety of Straight, Smooth, or V-Jaw styles.

SKU	Overall Length	Jaw Opening	Jaw Length	Jaw Shape
140-430-BULK	10 in	2 in	1.38 in	430 [®] Straight
140-440-BULK	12 in	2.25 in	1.50 in	440 [®] Straight

Tubing Cutters

RIDGID

Constant Swing Tubing Cutters



Features:

- Features an enclosed feed screw to eliminate clogging and jamming, grooved rollers for close-to-flare cuts, and a fold-away reamer.
- X-CEL[®] Knob cuts tubing more quickly and easily with a larger, more ergonomic design.
- X-CEL[®] Wheel Pin, ball detent design, allows users to change cutter wheel quickly, no tool needed.
- Spare cutter wheel included in the knob.
- Made from high-strength zinc alloy.
- Cuts copper, brass, aluminum tubing, and thin-wall conduit. Cutting Cap.: 1/8 in - 1-1/8 in

Includes: Spare Cutter Wheel Stored in Knob

SKU	Jaw Material	Blade Material	
632-31622	Zinc Alloy	Steel	181



Glass Tube Cutters



- Designed to cut glass tube and brittle tubular materials from ¼ in to 1-1/2 inch.
- Based on the original Wheeler squeeze and pop principle.
- Replaceable chain.
- Cutting Cap.: 1/4 in 1 in

Includes: (1) Cutter; (1) Chain

828-79014



PRYING TOOLS



TRUE TEMPER

Pinch Point

Crowbars Features:

- Hardened, drop-forged steel construction.
- Heavy-duty tool for stubborn prying tasks and heavy lifting.
- Useful for breaking up hard surfaces.

Stock Size: 1-1/4 in

Tip Width: 1-1/4 in

Material: Heat Treated Carbon Steel



WRENCHES

Adjustable Wrenches

(CRESCENT

Adjustable Chrome Wrenches

Features:


- Wider knurl for easier adjustment.
- Laser etched scale provides a quick and convenient way to determine fastener size in either SAE or metric.
- Wide capacity jaw provides versatility to accommodate a greater size range of fasteners.
- · Wider handle provides more comfort and less hand fatigue.

Head Angle: 22-1/2° +/- 5°

Handle Type: Non-Cushioned

Material: Heat Treated Alloy Steel

Jaw Material	Blade Material	SKU	Opening Size	Overall Length
Zinc Alloy	Steel	181-AC212BK	1-1/2 in	12 in



RIDGID

Adjustable Wrenches

Features:

- Forged and Heat-treated for durability.
- Jaw scales in SAE and metric for quick adjustment.

Head Angle: 22.5°

Handle Type: Solid Steel

Material: Chrome-Vanadium Alloy Steel

SKU	Opening Size	Overall Length	Head Width	Head Thickness	Weight
632-86907	7/8 in	8 in	2 in	13.48 mm	1/2 lb
632-86912	1 1/8 in	10 in	3 in	15.88mm	3/4 lb
632-86917	1 5/16 in	12 in	3.75 in	19.05mm	11/2 lb
632-86922	1 11/16 in	15 in	4 in	25.40mm	3 lb
632-86927	2 1/16 in	18 in	4.75 in	30.94 mm	3 lb

Pipe Wrench Parts & Accessories

RIDGID

Pipe Wrench



Features:

- Wrench Hook Jaw is
- a genuine Ridgid[®] part for steel or aluminum pipe wrenches.
- Its teeth provide a strong, dependable grip on your conduits.

SKU	Pipe Cap.	Туре	Wrench Size	For Model
632-31675	2-1/2 in	Heel Jaw and Pin Assembly	18	E-18
632-31670	2-1/2 in	Hook Jaw	18	E-18
632-31700	3 in	Heel Jaw and Pin Assembly	24	E-24
632-31695	3 in	Hook Jaw	24	E-24
632-31710	3 in	Nut	24	E-24
632-31725	5 in	Heel Jaw and Pin Assembly	36	E-36
632-31720	5 in	Hook Jaw	36	E-36
632-31735	5 in	Nut	36	E-36
632-31750	6 in	Heel Jaw and Pin Assembly	48	48
632-31745	6 in	Hook Jaw	48	48
632-31775	8 in	Heel Jaw and Pin Assembly	60	60
632-31770	8 in	Hook Jaw	60	60

RIDGID

Aluminum Straight Pipe Wrenches

Features:

- Nearly 40% lighter than comparable cast-iron models.
- Jaws and all other parts identical to Ridgid heavy duty wrenches.

Material: Aluminum

Jaw Material: Alloy Steel

Handle Type: I-Beam

SKU	Pipe Cap.	Overall Length	Weight
632-31090	1-1/2 in	10 in	1 lb
632-47057	2 in	12 in	2-1/2 lb
632-31095	2 in	14 in	2-1/2 lb
632-31100	2-1/2 in	18 in	3-3/4 lb
632-31105	3 in	24 in	6 lb
632-31110	5 in	36 in	11 lb
632-31115	6 in	48 in	18-1/2 lb

Heavy-Duty Straight Pipe Wrenches

Features:

- Instant grip/release.
- Heat-treated replaceable jaw.
- Easy spin nonstick adjustment nut.
- Fully floating forged hook jaw.
- Replaceable hook and heel jaws.

Material: Cast Iron Handle

Jaw Material: Steel

Handle Type: I-Beam

SKU	Pipe Cap.	Overall Length
632-31000	3/4 in	6 in
632-31005	1 in	8 in
632-31010	1-1/2 in	10 in
632-31015	2 in	12 in
632-31020	2 in	14 in
632-31025	2-1/2 in	18 in
632-31030	3 in	24 in
632-31035	5 in	36 in
632-31040	6 in	48 in
632-31045	8 in	60 in



CRAYONS

PAINTSTIK B

MARKAL

Paintstik[®] Original B[®] Solid Paint Markers



Features:

- Solid paint marker combines the durability of paint in the convenience of a crayon.
- Superior marking performance on oily, icy, wet, dry, or cold surfaces.
- Weather-resistant and UV-resistant for long-lasting marks.
- Works on rough, rusty, or dirty surfaces.

Length: 4-3/4 in

Temp. Range: -50° F - 150° F

Flash Point: 204° C

Dia: 11/16 in

SKU	Color
434-80220	White
434-80221	Yellow

MARKERS

BRITE-MARK

DYKEM

BRITE-MARK® Medium

Paint Markers

Features:

- Make permanent bright marks on metal, rubber, plastic, glass, concrete, leather, stone, wood, vinyl and more.
- Formula is not xylene-based.
- Valve actuated mechanism prevents paint in barrel from drying when cap is left off.
- Heavy duty aluminum body with large paint capacity.
- Ideal for color coding.
- Bullet tips are replaceable to ensure complete use of paint in each marker.
- Drying Time: 25 35 seconds.

Tip Size: Medium; Fiber #15

Tip Type: Bullet

Temp Range: 0° F - 350° F

SKU	Color
253-84003	White

MARKAĽ

Paint-Riter[®] Valve Action[®]

Paint Markers



Variety of colors for

Features:

improved mark identification, quality control, and parts inspection.

PAINT-RITER

- Fast-drying, permanent paint for immediate handling reduces work downtime.
- Xylene-free paint reduces user health risks and makes for a safer marking tool.
- Dura-Nib medium bullet tip resists wear to provide long marking life.
- Durable metal barrel and clip-cap reduce breakage and store easily in pocket.

Tip Size: 1/8 in

Tip Type: Round Bullet

Temp Range: -50° F - 150° F

SKU	Color
434-96820	White
434-96821	Yellow
434-96822	Red

COVERING PRODUCTS

Plastic Sheeting

POLY-COVER



Poly-Cover® Plastic Sheetings

Features:

- Tough plastic for tough jobs in construction and agriculture.
- Guaranteed to be full weight and thickness.

Width: 20 ft

Length: 100 ft

Material: Plastic

SKU	Thickness
795-4X10-C	4 mil
795-4X20-C	4 mil
795-6X10-C	6 mil
795-6X20-C	6 mil

Tarps



Multiple Use Tarps

Features:

- Sun and fade resistant.
- Rot and rust proof.
- Reinforced hem.
- Grommets every 3 ft.
- Material: Polyethylene

Thickness: 5 mil

SKU	Length	Width
101-0608	8 ft	6 ft
101-0810	10 ft	8 ft
101-1012	12 ft	10 ft
101-1016	16 ft	10 ft

Protective Tarps



Features:

- Protect or conceal your equipment or supplies while eliminating condensation.
- All double-stitched seams and hems with brass tie-down grommets spaced approximately 24 inches apart all around.

Material: Canvas Thickness: 25 mil

SKU	Length	Width
103-92561	10 ft	8 ft
103-92562	12 ft	10 ft

FITTINGS & ACCESSORIES

Fittings



Sight Glasses

Features:

- Allows the pumper and water hauler to see what is flowing through drain lines at all times.
- This type of plastic has more than 30 times the impact resistance of safety glass.
- Withstands prolonged exposure to ultraviolet rays.

Material: Polycarbonate

SKU	Outside Diam	Length
306-SG0500	2 in	8 in
306-SG0500-3	3 in	8 in
306-SG0500-4	4 in	8 in

TUBING

Gage Glass

GAGE GLASS

SCHOTT DURAN[®] Red Line Gage Glasses

Features:

- Has a red line between two white lines which when in the presence of a colorless liquid, magnifies the red line, making it easier to read liquid level.
- Redline tubular gage glass is widely used in tanks, reservoirs, and low-pressure boiler applications.
- No corrosion.
- Material: Glass

SKU	Outside Diam	Length
055-58X48RL	5/8 in	48 in

BABBIT & LADLES

METALS

Babbits



Weight

50 lbs

Features:

- General purpose bar.
- Industrial high strength and corrosion-resistant.
- Easy to cast.
- Wt.: 50 lb









Coco Mats

Features:

- Heavy-duty.
- Tough absorbent
- fibers hold up under any type of foot traffic.

Mildew resistant.

Height: 1-1/2 in

Material: Densely Woven Fibers

SKU	Length	Width
103-AB-GDN-3	30 in	18 in
103-AB-GDN-5	36 in	22 in
103-AB-GDN-9	48 in	30 in



GAGE POLES

BAGBA STICKI

Gage Poles

Features:

- Dependable measurement.
- Reliable quality.

Material: Wood

SKU	Length	Туре
030-AG10-1	10 ft	1-Pc
030-AG12-1	12 ft	1-Pc
030-AG12-2	12 ft	2-Pc
030-AG16-1	16 ft	1-Pc

and the state of the state

PACKING HOOKS

c.s. OSBORNE & CO. Flexible Packing Hook



- Features:
 Two spiral steel shafts, one inside of the other, wound in opposite directions.
- Handle is solid zinc.
- Hook is tempered and permanently pointed.
- Shank Diam: 5/32 in; 1/4 in; 3/8 in

Spiral Diam: 1/4 in; 5/16 in; 3/8 in

Spiral Length: 3/4 in; 1-1/8 in; 1-5/8 in

SKU	Size Group	Overall Length
565-1203	1; 2; 3	7-1/4 in; 10-3/4 in; 15-1/4 in

Flexible Packing Hooks

Features:

- Two spiral steel shafts, one inside of the other, wound in opposite directions.
- Handle is solid zinc.
- Hook is tempered and permanently pointed.

SKU	Overall Length	Shank Diam	Spiral Diam	Spiral Length
565-1204-1	7-1/4 in	5/32 in	1/4 in	3/4 in
565-1204-2	10-3/4 in	1/4 in	5/16 in	1-1/8 in
565-1204-3	15-1/4 in	3/8 in	3/8 in	1-5/8 in

RIG WASH & CREME BEADS



Creme Beads Granular Detergents

Features:

- Surfactants are biodegradable.
 Spray dried to homogenize ingredients
- and produce hollow beads that are extremely soluble even in cold water.
- Averages 5.6 phosphorus.



SKU	Capacity Vol.
103-AB-CB100	100 lb

Rig Washing Detergents

Features:

- Super Heavy-Duty Concentrate.
- Cuts through heavy oils, grease and drill muds.
- Helps equipment run at optimum levels.
- For use in on and off shore drilling rigs.
- Eliminates residue on pumps, pads and jacks, platforms, derricks, liners, casings, crown and traveling blocks and blow out preventers.
- Dilutions vary depending on application, optimum dilution 1 to 6 ounces per gallon.
- Can be diluted and used in spray bottles.

SKU 103-AB-RW50		Capacity Vol. 50 lb
	SAFETY PINS	
The Right Connection® Air King® Safety Features: • Heavy duty and oversi • Easy to use.		
SKU 238-AKSP25	Length 2-3/4 in	Width 5/8 in



HAND TOOLS

SAMPLE BAGS



Geological Sample Bags and Parts Bags

Features:

- Oilfield geological sample bags.
- All purpose bag for nuts, bolts, washers, and fittings.
- High count cloth, bleached and back filled.
- Strong white drawstring.

Quantity: 100 Bags per dispenser

SKU	Width	Length
485-41/2X6	4-1/2 in	6 in
485-5X7	5 in	7 in

SAND STRAINERS



Features:

- Triple seal assembly eliminates failure due to heat or mechanically induced stress.
- Copper core center.

Shell Material: Triple Coated Zinc Plated

Туре
RN5C
W18
D23
W89D



COMPRESSORS, BLOW GUNS, HOSES & FITTINGS

Air Hose Fittings





King Cable® Safety Cables

Features:

- King Cable® is the low cost answer to eliminate injuries by broken air hose connections.
- Highly resistant to rust and corrosion.
- No tools needed easy to install and remove.

Body Material: Galvanized Carbon Steel

Operating Pressure: 200 psi

SKU	Cable/Wire Size
238-WA2	1/4 in
238-WB1	1/8 in

CORDLESS TOOL BATTERIES & CHARGERS

Batteries, Cordless Tool



M18[™] REDLITHIUM[™] HIGH OUTPUT[™] HD 12.0 **Battery Packs**



Features:

- Best-in-class construction: offers long-lasting performance and the best protection against jobsite conditions.
- Fuel gauge Onboard: displays remaining run-time.
- Versatility: powers more than 150 M18[™] cordless solutions.
- For Model: Milwaukee[®] M18[™] Cordless Power Tools

SKU	Voltage	Batt. Cap.
495-48-11-1812	18 V DC	12.0 Ah



M18[™] REDLITHIUM[™] XC 5.0 Ah Extended Capacity Battery 2-Pack



- Features:
- REDLINK⁻ Intelligence provides optimized performance and overload protection using total system communication between tool, battery and charger.
- Best-in-class construction; offers long-lasting
- performance and durability. Onboard fuel gauge displays remaining runtime
- for less downtime on the job.
- Its all-weather performance capability delivers fade-free power in extreme jobsite conditions.

Batt. Type: Lithium-lon

For Model: Milwaukee[®] M18[™] Cordless Power Tools

W 1	
Voltage	Batt. Cap.
18V	5 A-h
	Voltage 18V

DRILLING & FASTENING TOOLS

Wrenches



M18 FUEL[®] w/ONE-KEY[®] High Torque Impact Wrenches 3/4 in Friction Ring



- Features: ■ ONE-KEY[™] compatible to
- customize, track and manage tool's performance and location.
 POWERSTATE[®] brushless motor delivers up to 1200 ft·lb of
- fastening torque and 1500 ft-lb of nut-busting torque.
- Features a friction ring with thru-hole design to ensure quick and easy socket changes.
- Easily toggle up to four custom performance profiles that can be saved to the memory of the tool.
- Premium rubber over-mold withstands corrosive materials and provides increased comfort when in use.
- LED light to illuminate the work area.
- Available as tool only or kit.

Voltage: 18 V DC

Batt. Type: Lithium Ion

Speed: 1800 RPM

Torque: 1600 ft·lb

Control Type: Trigger

Includes: (1) M18 FUEL[®] w/ONE-KEY[®] High Torque Impact Wrench 3/4 in Friction Ring Bare Tool (2864-20); (2) M18[®] REDLITHIUM[®] XC5.0 Resistant Capacity Battery Pack (48-11-1850R); (1) M18[®] and M12[®] Multi-Voltage Charger (48-59-1812)

SKU	Drive Size	Drive Type
495-2864-22R	3/4 in	Square



M18[™] FUEL[™] 1 in High Torque Cordless Impact Wrenches w/ONE-KEY[™]



Features:

- POWERSTATE[®] Brushless Motor delivers up to 1,800 ft·lb nut-busting torque.
- ONE-KEY" Compatible allowing ability to customize, track and manage tools for increased productivity and investment protection, includes the ability to set a repeatable torque output for maximum control.
- 4-Mode DRIVE CONTROL[∞] provides greater control over output speed and power.
- REDLINK PLUS[®] Intelligence ensures maximum performance and protects from overloads, heating and over-discharge.
- Handle rotates 270 degrees and easily adjusts without a tool.
- LED light to illuminate the work area.
- Premium rubber overmold withstands corrosive materials and provides increased comfort when in use.
- Eliminates compressors and generators, providing greater portability and lower cost of ownership.
- Integrated lanyard loop allows for safer use and easier storage.
- Compatible with all M18[™] batteries.
- Available as tool only or kit.

Voltage: 18 V DC

Batt. Type: M18" REDLITHIUM" HIGH OUTPUT" XC8.0 Speed: 1,650 RPM

Cycle Rate: 2,450 IPM

Torque: 1,500 ft-lb Fastening; 1,800 ft-lb Nut Busting

Control Type: 4-Mode Customizable

Includes: (1) M18 FUEL[®] 1" High Torque Impact Wrench w/ ONE-KEY[®] (2867-20); (2) M18[®] REDLITHIUM[®] HIGH OUTPUT[®] XC8.0 Battery Packs (48-11-1880), Tool-Free Adjustable Handle; (1) Lanyard Loop; (1) Rapid Charger; (1) Contractor Bag

SKU	Drive Size	Drive Type
495-2867-22	1 in	Square

FINISHING TOOLS

Grinders

DEWALT.

4.7 hp Large Angle Grinders

Features:

- Motor provides overload protection.
- Dust Ejection System[™].
- Anti-Vibe trigger handle.
- Lightweight design.
- Automatic turn-off brushes.

SKU	Wheel Dia	Amps	Includes
115-DWE4557	7 in	15 A	7 in Guard; 3 Position Side Handle
115-DWE4559N	9 in	15 A	9 in Guard; 3-Position Side Handle



DRIVEN TO OUTPERFORM.

M18 FUEL[™] is engineered for the most demanding tradesmen in the world. Delivering unrivaled performance in a compact REDLITHIUM[™] Battery Pack and REDLINK PLUS[™] Intelligence Hardware and Software - that deliver unmatched power, run-time and durability. The M18 FUELT 4-1/2" / 5" Dual-Trigger Braking Grinder is the next advancement in angle grinders, providing greater control through dual-trigger activation, a permanent side handle, and AUTOSTOP™ kickback control.





DUAL-TRIGGER TWO-HANDED OPERATION





ROVIDES 15 POSITIONS



OSTOP[™] CONTROL, ADVANCED KICKBACK PROTECTION



SPECIFICATIONS

DESCRIPTION	SPECIFICATIONS	DESCRIPTION	SPECIFICATIONS
No Load RPM	3,500 - 8,500	Variable Speed	Yes
Wheel Diameter	4-1/2" / 5"	ONE-KEY™	Yes
Switch Type	Dual Paddle, No-Lock	Length (Tool-Only)	14.1"
AUTOSTOP [™] Kickback Protection	Yes	Width (Teel Only)	5.2" (Handle In)
RAPIDSTOP [™] Brake	Yes	Width (Tool-Only)	10.3" (Handle Out)
E-Clutch	Yes	Height (Tool-Only)	5.4"
Overload Protection	Yes	Weight (Tool-Only)	5 lbs



M18 FUEL 4-1/2" / 5" Dual-Trigger Braking Grinder (Tool-Only) 495-2986-20 Includes: 2986-20 4-1/2" / 5" Enhanced Safety Grinder, T27 Guard, T1 Clip-On Guard, Back Flange, Wrench and Flange Nut. Battery and Charger Not Included.



DEWALT

Small Angle Grinders

Features:

- 11 Amp AC/DC 11,000 RPM motor designed for faster material removal and higher overload protection.
- Low profile gear case allows tool to fit into tight spaces.
- Quick-Change[®] Wheel Release provides easier and quicker wheel removal without the need for a wrench.

Watts: 1400 W

Speed: 11000 RPM

Spindle Thread: 5/8 in - 11

SKU	Wheel Dia	Amps	Includes
115-DWE402	4-1/2 in	11 A	2-Position Side Handle; 4-1/2 in One-Touch [™] Type 27 Guard
115-DWE402N	4-1/2 in	11 A	One-Touch [®] Guard; 2-Position Side Handle; Wrench



M18 FUEL[®] 4-1/2 in and 5 in Cordless Angle Grinders



Features:

- POWERSTATE[™] brushless motor, purposely built for the M18
 - FUEL[™] 4-1/2 in and 5

in angle grinder, delivers 8,500 RPM to provide the power to complete the toughest grinding and cutting applications.

- REDLINK PLUS[®] Intelligence enables communication between batteries and tools, allowing for unmatched levels of performance, protection, and compatibility.
- Tool-free accessory changes with Integrated FIXTEC Nut Technology.
- Electronic clutch for kickback protection.
- Anti-vibration side handle for increased user comfort and safety.
- Overload protection to maximize motor life.
- Compatible with all M18[™] batteries.
- Options available for bare tool only or kit with 2 M18^{**} REDLITHIUM^{**} HIGH OUTPUT^{**} XC6.0 battery packs.

Batt. Type: Lithium-Ion

Speed: 8500 RPM

Control Type: Paddle

Includes: (1) M18 FUEL[®] 4-1/2 in/ 5 in Grinder Paddle Switch, No-Lock; (2) M18 REDLITHIUM[®] HIGH OUTPUT[®] XC6.0 Battery Pack; (1) M18[®] & M12[®] Rapid Charger; (1) T27 Guard; (1) T1 Clip-On Guard; (1) Side Handle; (1) Wrench; (1) Back Flange; (1) Flange Nut; (1) Contractor Bag

SKU	Voltage	Spindle Thread
495-2880-22	18V DC	5/8 in - 11 UNC
^^		

PUMPING EQUIPMENT

Fuel Pumps

FILL-RITE

Piston Hand Pumps

Features:

TWALT

- Anti-siphoning valve.
- Check valve and strainer.
- Pump may be padlocked.
- Steel handle and wood grip.
- Pump can be set up for reverse flow.
- Adaptable

for drums, kegs, and storage tanks. Flow: 20 gal/min

Outlet Size: 3/4 in (NPT)

Inlet Size: 1 in (NPT) Hose Length: 8 ft

Housing Material: Aluminum Body w/Stainless Steel Liner

Seal Material: Stainless Steel

Designated Fluid: Oil; Fuel

Includes: 3/4 in Outlet; 8 ft Hose and Nozzle

SKU	Vol. @ No. of Strokes
285-FR152	20 gal @ 100

Rotary Hand Pumps

Features:

- Anti-siphoning valve.
- Check valve and strainer.
- Pump may be padlocked.
- Pump can be set up for reverse flow.
- Compatible with diesel, E15, kerosene, B20 and light oils.
- Adaptable for drums, kegs, and storage tanks.
- Series 800C meter is available.

Flow: 10 gpa (38L)

Outlet Size: 3/4 in (NPT)

Inlet Size: 1 in (NPT)


Hose Length: 8 ft

Housing Material: Aluminum

Designated Fluid: Diesel Fuel; Gasoline; Light Oil; Kerosene

Includes: 20 in to 34-3/4 in Steel Telescoping Suction Pipe; 5/8 in x 8 ft UL Listed Hose with Static Ground Wire; Gallon Counter; PTFE Tape Roll

SKU	Vol. @ No. of Strokes
285-FR112	10 gal @ 100





CLOTHING PROTECTION

Coveralls & Overalls

Tyvek.

Tyvek[®] 400 Coveralls

Features:

- Composed of Tyvek[®] 400 flash-spun, high-density polyethylene which creates a unique, nonwoven material.
- Offers inherent barrier against particles down to 1.0 micron in size.
- Protection built into the fabric itself, no films or laminates to abrade or wear away.
- Comfort fit design enables a greater range of movement while stretching and bending with reinforcement in high stress areas.
- Available in more styles and sizes.

Material: Tyvek® 400

SKU	Size Group	Style
251-TY120S-XL	X-Large	Searged Seams; Collar; Elastic Waist; Zipper Front; Open Wrists and Ankles; Storm Flap
251-TY120S-2XL	2X-Large	Searged Seams; Collar; Elastic Waist; Zipper Front; Open Wrists and Ankles; Storm Flap
251-TY122S-2XL	2X-Large	Serged Seams; Attached Hood (Respirator Fit); Attached Skid-Resistant Boot; Elastic Waist, Wrists, Ankles; Front Zipper; Storm Flap

Rainwear



3-Pc Rainsuits

Features:

- Jacket is vented back for breathability, duo-layer front closer to prevent wet, two front patch pockets for storage, and a corduroy collar for comfort.
- Removable hood with drawstring.
- Adjustable suspenders for overalls with triangular buckles for perfect fit and single snap fly.

Material: PVC Over Polyester

SKU	Size Group
101-9000-L	Large
101-9000-XL	X-Large
101-9000-2XL	2X-Large

EAR PROTECTION

Earplugs

3M

3M[®] E-A-R[®] UltraFit[®] Earplugs 340-4004

Features:

- Conforms to oval shape of ear.
- No rolling or touching plug portion during insertion.
- Proprietary, premolded, triple-flange earplug design inserts easily and provides a comfortable fit for a reusable earplug.
 Quantity: 100 Pairs per Box

SKUNoise ReductionBody Material247-340-400425 dBElastomeric Polymer

3M[™] Tri-Flange[™] Earplugs P3001

Features:

- Flexible flanges conform to the ear canal for custom fit.
- Pliable, premolded material ensures clean and comfortable hearing.
- Stem provides quick and clean insertion/removal.

Quantity: 100 Pairs per Box

SKU	Noise Reduction	Body Material
247-P3001	26 dB	Elastomeric Polymer

Honeywell Howard LEIGHT

MAXIMUM Disposable Earplugs

Features:

- Contoured design easier to insert, resists tendency to back out of ear canal.
- Polyurethane foam enhances

comfort, especially for long-term wear.

- Smooth, soil-resistant closed cell-foam skin prevents dirt build-up.
- Bell shape delivers maximum in-ear comfort.
- Also available in small size.

Material: Polyurethane Foam

SKU	Noise Reduction	Туре	Quantity
154-MAX-1	33 dB	Uncorded	200 Pairs per Box
154-MAX-30	33 dB	Corded	100 Pairs per Box





MAXIMUM LITE Disposable Earplugs

Features:

- Low pressure polyurethane foam expands gently for comfortable long-term wear.
- Contoured T-shape
- for easy insertion and wear.
- Smooth, soil-resistant closed cell-foam skin prevents dirt build-up. Material: Foam

Noise Reduction: 30 dB

SKU	Туре	Quantity
154-LPF-1-D	Uncorded	500 Pairs per Box
154-LPF-30	Corded	100 Pairs per Box

Quiet[®] Reusable Earplugs

Features:

- Patented "no-roll" design is easy to handle and fit.
- Contoured shape comfortably matches contours of the ear canal.
- Built-in insertion stem makes insertion quick and easy.
- Smooth, non-irritating skin provides all-day comfort, easy to clean for long-term use.

Quantity: 100 Pairs per Box

SKU	Noise Reduction	Body Material
154-QD30	26 dB	Foam

EYE PROTECTION

Safety Glass Parts & Accessories



Lens Cleaning Towelette Dispensers

Features:

 Pre-moistened with C-Clear Anti-Fog, Anti-Static formula for use on plastic, polycarbonate and glass lenses.



 Strategic placement of towelette dispensers throughout a facility will promote proper lens cleaning habits

and extend the life of prescription and non-prescription eyewear.

- Contains no silicone.
- Safe and effective with all lens coatings including Anti-Reflective Coating.
- Also good for use on goggles, face shields, CRT screens and microscopes.

Width: 5 in

34

 SKU
 Includes
 Length

 101-70-AB
 100 Individuals per Dispenser
 8 in

Safety Glasses



V30 Nemesis[™] Safety Glasses



Features:

- Safety glasses feature a sporty, flexible, lightweight design.
- Wraparound frame has a base curve of 8 that extends the range of peripheral protection, as well as soft touch temples for comfort.
- Patented FLEX-DRY* nose piece designed to be extremely flexible, to channel sweat away from the eyes, and to help prevent slippage down the nose for long-term comfort.
- Polycarbonate lenses provide 99.9% UVA/UVB/UVC protection.
- Includes neck cord for securing them, so that the glasses are ready to protect at a moment's notice.

Lens Material: Polycarbonate

SKU	Lens Tint	Lens Coating/Shade
412-25676	Clear	Uncoated
412-25685	Indoor/Outdoor	Uncoated
412-25688	Smoke Mirror	Mirror
412-22475	Smoke	Anti-Fog
412-25679	Clear	Anti-Fog
412-22475	Smoke	Anti-Fog

FALL PROTECTION

Fall Protection Parts & Accessories

Honeywell Miller

Poly Ropes

Features:

- Meets all applicable OSHA, ANSI and CSA standards.
- Strong and durable.
- Tagline poly rope for
- self-retracting lifeline.

Material: Polypropylene



SKU	Applications
493-193R/130FTYL	Self Retracting Lifelines

FIRE, GAS & WATER PROTECTION

Detectors

Honeywell THE POWER OF CONNECTED

Clip Single-Gas Detectors

Features:

- One button operation.
- Operates up to two years use without calibration, sensor replacement, or battery recharging/replacement.
- Wide angle flash which alerts simultaneously with audible and vibrating alarm.
- Automatic
- logging of the 35 most recent gas events.
- Compatible with IntelliDoX, Fleet Manager II Software.

Gas Type: Hydrogen Sulfide Temp. Range: -40° F - 122° F Sound Level: 95 dBA Display Type: LCD Power Source: Lithium Battery Run Time: 2 Years

SKU	Includes	Sensor Type
126-BWC2-H	Specified Sensor; Stainless Steel Alligator Clip; Concussion-Proof Housing: Test Cap: Instructions	Surecell [™]

Fire Extinguishers



ProLine[™] Multi-Purpose **Dry Chemical Fire Extinguishers**

Features:

- Rechargeable.
- Designed to meet most commercial and industrial specifications.
- Tough impact resistant metal valve, handle and lever.
- Powder coated cylinder for corrosion protection.
- Easy-to-read gauge.

Fire Type: Class A, B and C Fires Mounting Position: Upright

Operating Temp.: -40° F - 120° F Operating Distance: 16 ft - 20 ft

Extinguishing Material: Monoammonium Phosphate

Capacity Wt.
10 lb
20 lb

Gloves Features:

ANCHOR

 Cotton/polyester construction is breathable and decreases hand fatigue.

with Nap-In Finish

Knit wrist helps prevent dirt and debris from entering the glove.

HAND PROTECTION

Gloves

- Clute cut provides a roomy fit and straight thumb increases comfort in closed-fisted work.
- Double palm provides additional weight, durability, and protection.
- Nap-in finish offers greater durability due to its higher abrasion resistance.
- Multi-purpose glove used for light protection.

Cuff Style: Knit-Wrist

Style: Clute Cut; Straight Thumb

SKU	Size Group	Material
101-1060	Large	Cotton/Polyester; Fully Corded

HEAD/FACE PROTECTION

Faceshields & Visors

JACKSON[®]

F30 Acetate Faceshields

Features:

- Ideal for scratch resistance and premium optics.
- High-grade cast sheet acetate protects against splash.
- 99.9% UV protection.
- Binding: Bound


Used With: Jackson Safety Headgear Length: 15-1/2 in Height: 9 in Thickness: 0.047 in Model: 3440 BULK

SKU	Lens Material
138-29091	Acetate









MORE

Hard Hat & Cap Parts & Accessories



Fas-Trac[®] III Replacement Suspensions



Features:

- Ratchet suspension and flush rear lug
- attachments eliminate pressure points for additional wearer comfort.
- Three levels of nape strap adjustment ensure a customized fit.
- Graspable ratchet with ultra-smooth rotation and steadfast hold.

Material: Plastic/Nylon

SKU	Used With	Suspension
454-10148708	V-Gard [®] ; V-Gard 500; V-Gard GREEN; SmoothDome [®]	4-Point Ratchet
454-10148708	GREEN; SmoothDome®	4-Point

Hard Hats & Caps



Skullgard[®] Protective Caps and Hats



- Strong, protective hats offer outstanding
- protection in hot, dangerous industries.
- Tested to radiant heat loads producing temperatures up to, but not exceeding, 350F.
- Smooth crown allows easy use of MSA welding equipment.
- Heavy duty construction produces a sturdy, reliable product for long-lasting use.

Adjusting Method: Ratchet

Material: Phenolic

Size Group: Standard; 6-1/2 to 8

SKU	Suspension
454-475407	Fas-Trac [®] Ratchet

V-Gard[®] Protective Hats

Features:

36

- Convenient caps and hats provide comfortable, lightweight protection.
- Polyethylene shell provides superior impact protection.
- Available with Fas-Trac[®] III or Staz-On[®] suspension.

Adjusting Method: Ratchet Material: Polyethylene Size Group: Standard; 6-1/2 to 8



Escape Respirators



W65 Self-Rescuer Respirators

Features:

- Provides emergency respiratory protection against carbon monoxide gas resulting from underground fires or explosions.
- One time use device for escape purposes only.
- Protected by a rugged stainless steel case.
- Do not use in atmospheres containing less than 19.5% oxygen or in atmospheres containing other toxic gases and vapors.

Includes: Protective Steel Case

Body material: Noble Metal Catalys; Hopcalite Pre-Filter (W 95)

SKU 454-455299

Resistance Carbon Monoxide

RESPIRATORY PROTECTION

Cartridge Respirators



3M[®] Half Facepiece Disposable Respirator Assembly 53P71



Features:

- Resealable storage bag helps keep respirator clean between uses.
- Low profile design provides wider field of vision and greater comfort while wearing goggles or glasses.
- Can be used with NIOSH P95 and P100 filters for oil and non-oil particles.
- For convenience and simplicity, some 3M respirator package assemblies are packaged with either P95 or P100 filters along with 501 filter retainers or 502 filter adapters.

Body Material: Thermoplastic Elastomer Includes: P95 Filter: 501 Filter Retainers

SKU	Protected Area	Size Group
142-53P71	Half Facepiece	Large

SKU 454-475369

Disposable Respirators

3M

3M[™] Particulate Respirator 8210

Features:

- Two-strap design with single point attachment helps provide a secure fit.
- Adjustable noseclip reduces eyewear fogging and helps ensure a better fit and seal.
- Lightweight construction enhances worker comfort and wear time.
- Patented filter media with advanced electrostatically charged microfibers help make breathing easier and cooler for enhanced user comfort.

Size Group: One Size

Suspension: Two Fixed Straps

Quantity: 20 Respirators per Box

Includes: Adjustable Noseclip

SKU	Protected Area	Filtration Grade
142-8210	Half Facepiece	N95

TORCH & WEED BURNERS

WESTERN a Scott Fetzer company

Hotspotter All Purpose Propane Torches

Features:

- Flame tools are for exterior maintenance and repair.
- Hotspotter is an all-purpose propane torch that delivers at full cylinder pressure with no smoke and no fumes.
- Ergonomic handle with adjustable trigger.
- Hooks up to standard 20-pound propane tank.

Gas Type: Propane

Handle Length: 31 in

Hose Length: 10 ft

Includes: Brass Propane Tank Adaptor; Brass Flow Control Shut-Off Valve; Spark Ignitor; Cast Iron and Steel Nozzle; Hose

```
312-WB-101
```

Output Power 500000 Btu

SAFETY STORAGE

Safety Cans

🕢 Justrite.

Type I Steel Safety Cans

Features:

- Color coding avoids accidents.
- Self-closing lid controls spills.
- Leakproof, auto-venting lid prevents explosion.
- Available with funnel for cans 1 gal or larger.
- Cans up to 1 quart feature
- a trigger-release handle, while larger capacities have a swinging handle to greatly ease carrying of heavier loads.

Dia.: 11.75 in

Height: 16.875 in

Material: 24-ga Galvanized Steel

Capacity Vol.: 5 gal

SKU	Includes
400-7150100	Stainless Steel Flame Arrestor; Swinging Handle
400-7150200	Stainless Steel Flame Arrestor; Swinging Handle
400-7150110	Poly Funnel; Stainless Steel Flame Arrestor; Swinging Handle

Type II AccuFlow[™] Safety Cans

Features:

- Color coding avoids accidents.
- Stainless steel flame arrester prevents flashback ignition.
- Easy-to-use Safe-Squeeze[®] trigger for controlled pouring.
- Two-openings, one for targeted pouring, one with ergonomically designed lift-lever for easy filling.

Dia.: 11.75 in

Height: 17.5 in

Hose O.D.: 1 in Material: 24 ga Galvanized Steel Includes: Flexible Metal Hose Capacity Vol.: 5 gal

apacity vol. 5 gai

400-7250130 400-7250230



THE V-Gard C1[™] HARD HAT

A higher degree of heat stress protection. The patent-pending ReflectIR[™] Thermal Barrier works to block the energy of the sun, keeping the inside of the hard hat up to 20°F (11°C) cooler, reducing the risk of heat stress. Find where to buy at www.msasafety.com/vgardcl.



Sweat Bands



Headgear Sweatbands

Features:

- Individually packaged.
- Hook & loop closure allows the fit onto most major brand headgear.
- Sweat absorbent air cushioned layer lined with 100% fleece cotton. **Used With**: Suspension Headgear

SKU	Strap Type
101-SB320V	Hook and Loop

LOCKING DEVICES

Padlocks & Cables



Sesamee[®] Keyless Padlocks

Features:

- All-brass internal mechanisms for non-corrosive durability.
- Lifetime guarantee.
- You set the combination
- Shackle Diam: 5/16 in

Shackle Inner Width: 1 in

Shackle Material: Hardened Steel

Shackle Length
1 in
2-1/4 in

Master

No. 175 Combination Brass Padlocks

Features:

- Set-your-own combination convenience.
- Resettable to any of 10,000 personalized combinations.

Shackle Diam: 5/16 in

Shackle Inner Width: 1 in Shackle Material: Hardened Steel Code Format: 4 Step Dial Shackle Length: 2-1/4 in

> SKU 470-175DLH 470-175LH

GATORADE

20 oz Wide Mouth Bottles

Features:

- Make a refreshing beverage choice - this scientifically proven blend of carbohydrates and key electrolytes is designed to help
- athletes and active people hydrate, refuel and push through.
- Choose from a variety of delicious and refreshing fruity flavors.
 Works to rehydate, replenish and refuel after a hard workout.
- Capacity Vol: 20 oz

SKU Flavor 308-32866 Fruit Punch 308-32867 Orange 308-32868 Lemon-Lime 308-32482 Fierce Grape 308-32481 Cool Blue 308-20781 Fruit Punch, Orange, Lemon-Lime

HEAT STRESS PROTECTION

Activity Drinks

G Series O2 Perform[®] Thirst Quencher Instant Powder Variety Pack

Features:

- Hydrates with electrolytes that help them replace the carbs, electrolytes and fluids they lose when they sweat.
- Carbohydrates help
- stimulate rapid fluid absorption and fuel the active body. Flavor: Fruit Punch; Lemon-Lime; Orange; Frost Riptide Rush

SKU	Capacity Vol.
308-03944	21 oz



Sqwincher Sqweeze® Freezer Pops

Features:

- Great way to cool down the body during hot or fatiguing work situations.
- Just freeze and serve to administer
- a tasty way to provide electrolytes to any work crew.
- Formulated to be absorbed significantly faster than water, allowing the body to replenish electrolytes and minerals for proper hydration.

			-		
Flavor: Unerry; Grape; Lemon-Lime; Mixed Berry; Urange					

SKU	Capacity Vol.
690-159200201	3 oz

Items in this catalog are a selection of our core offerings. Additional sizes, colors, flavors, and scents may be available for certain items. Visit our website for additional product information.



SPILL CONTROL SAFETY

Sorbents

ANCHO

Oil-Only Sorbent Pads

Features:

 White absorbents pick up petroleum-based fluids. paints and non-water soluble chemicals while repelling water - great for indoor & outdoor use.

Length: 17 in

Width: 15 in



SKU	Туре	Quantity
103-AB-BP0500	Light-Weight	100 Pads per Bag
103-AB-BP0100	Heavy-Weight	100 Pads per Bag
103-AB-BP0200	Heavy-Weight	200 Pads per Bag

Universal Sorbent Pads

Features:

 Highly versatile, grey absorbents pick up water-based, petroleum-based and non-aggressive, chemical fluids.

Length: 17 in

Width: 15 in

40

SKU	Туре	Quantity
103-AB-BPU200	Light-Weight	200 Pads per Bag
103-AB-BPU500	Light-Weight	100 Pads per Bag
103-AB-BPU100	Heavy-Weight	100 Pads per Bag

BRUSHING & SWEEPING PRODUCTS

Brushes & Brooms



Dope Brushes

Features:

- Hang-up hole in handle.
- Useful for applying pipe dope and other industrial applications.

Block Material: Wood

Handle Length: 16 in

Bristle Material: Gray Tampico

Fiber

Includes: Tapered Ends

SKU	Bristle Length	Block Length
455-4-DOPE	2 in	2 in
455-2-DOPE	2-1/2 in	2-1/2 in

Fender Wash Brushes

Features:

- Safe, scratch-resistant
- natural bristles (except for chrome or clear coat paint surfaces).
- Ideal for cleaning fenders, wheels and wheel wells.
- Hang-up hole in handle.
- Block Material: Hardwood

Block Finish: Wax Tumbled

Handle Length: 20 in

Bristle Length: 2 in

Block Width: 3 in

SKU	Bristle Material
455-20T	White Tampico

Utility Brushes

Features:

- Angled handle protects hands and knuckles.
- Finger grip handle.
- Hang-up hole in handle.
- Block Material: Plastic

Bristle Length: 2 in

Block Length: 20 in

SKU	Bristle Material
455-73-N	White Nylon

CLEANING PRODUCTS

Detergents



Liquid Laundry Detergents

Features:

- High-powered, grease-cutting formula removes tough institutional stains.
- Fluorescent whitening agents help maintain whiteness and brightness.

608-40217

- Phosphate-free.
- Safe for septic systems.



Capacity Vol

92 oz

Floor and All-Purpose

1

t tout usage

Floor and All-Purpose Cleaners

Features:

- High levels of surfactant and builders combined to cut through tough grease.
- Easy-rinse powder formula is ideal for quarry tile.
- Cleans floors, walls, pots and pans.
- Can be used with chlorine bleach and contains no phosphates.
- Chemical Compound: Alkyl Benzene Sulfonate; Sodium Carbonate

SKU	Capacity Vol.
608-02364	36 lb

Dishwashing Cleaners



Manual Pot & Pan Dish Detergents

Features:

- The grease-fighting power of Dawn[®] dish soap, specifically formulated for tough business jobs.
- Long lasting suds provide greater cleaning capacity with less sink changeover.

SKU	Capacity Vol.
608-45112	38 oz
608-57445	l gal
608-70681	5 gal

CLOROX

Disinfectant Wipes

Features:

- One-step cleaning and disinfecting.
- Bleach-free formula kills 99.9% of
- bacteria, including staph and salmonella.
 Ideal for day care centers, offices, schools and restaurants.

SKU	Quantity
863-CLOX01594	35 Wipes per Container

Disinfectants

Floor & Carpet Cleaners



Oil-Based Non-Sanded Floor Sweeping Compounds

Features:

- Non-abrasive sweeping compound safe to use on any floor.
- Perfect for collecting dirt and dust on all types of wood, tile, terrazzo, and finished concrete floors without scratching.

3KU 103-FLOOR-SWEEP

Capacity Vol 50 lb

LORO

PERSONAL HYGIENE

Hand Cleaners



Tub-O Towels[®] Multi Purpose Towels

Features:

- No water necessary.
- Contains lanolin, aloe vera & vitamin E.
- Kills germs.

Capacity Vol.: 45 oz

Quantity: 90 Wipes per Container

29

SKU	W x L Per She
6-TW90	10 in x 12 in







All Purpose Waterless Hand Cleaners

Features:

- Unique blend designed to clean the hands without harsh acids or alkalis.
- Works equally well with or without the use of water.
- Leaves hands looking and feeling clean, conditioned, and without the greasy feeling associated with most hand cleaners.

Capacity Vol 14 oz 407-105 407-101P 4 lb 5 oz


SCRUBS

Hand Cleaner Towels

Features:

- Clean, citrus-scented formula loosens and dissolves industrial soils while leaving hands free from dryness and irritation.
- Rough Touch[®] blue towel locks in soil to prevent it from transferring back onto hands and surfaces.
- Hands are left feeling clean with no sticky residue and no rinsing required.

Quantity: 72 Wipes per Container





Multi-Purpose Scrubbing Wipes

Features:

- Extra large, durable wipes, 10 inch x 12 inch.
- Multi-purpose to use on hands, tools, and surfaces.
- Contains no harsh chemicals.

Quantity: 72 Wipes per Container

Used With: Hands; Surfaces; Tools

SKU	W x L per sheet
103-360726	10 in x 12 in



Natural Orange[™] Pumice **Hand Cleaners**

Features:

- Pumice scrubbing particles get hands clean fast.
- Lotion formula provides powerful . yet gentle cleaning performance.

315-0955-04



WIPING PRODUCTS



🕸 Kimberly-Clark

PROFESSIONAL*

WypAll[®] L30 Wipers

Features:

- Ideal for general-purpose, light-duty cleanups.
- Removes soils and liquids from face and hands.

412-05843



CONTRACTO

Quantity

10.4 in x 11 in	70 Sheets per Roll

WASTE RECEPTACLES

W x L per sheet

Trash Can Liners



FLEX-O-BAG[®] Trash **Can Liners and Contractor Bags**



 Convenient large rolls of heavy industrial weight plastic bags in handy dispenser boxes and extra-long twist ties.

SKU	Capacity Vol.	Width	Quantity
795-FB33-100	33 gal	33 in	100 Bags per Dispenser
795-HB42-20	42 gal	33 in	20 Bags per Dispenser
795-HB55-30	55 gal	36 in	30 Bags per Dispenser
795-FB55-50	55 gal	36 in	50 Bags per Dispenser



SCRUB

ANCHOR

SCRUBS HAND CLEANER TOWELS

THE ORIGINAL WATERLESS CLEANER TOWEL



SCRUBS IN-A-BUCKET® HAND CLEANER TOWELS DO MORE THAN AN INCREDIBLE JOB OF **CLEANING - THEY SAVE YOU MONEY!**

They contribute to the bottom line because the vast majority of cleaning costs (more than 90%) are in labor! SCRUBS® towels allow workers to clean their hands ANYWHERE, ANYPLACE, ANYTIME![®], reducing the number of trips to hand-washing stations. The time saved can be used for more productive activities for your business.

AVAILABLE PRODUCT						
ORS Item #	MFG #	Net Contents	Packs/Case	Wipe Size		
253-42201	42201	1 Towel	100	8 x 12 in		
253-42230	42230	30 Towel	6	10 x 12 in		
253-42272	42272	72 Towel	6	10 x 12 in		

ASPHAIT









REMOVES









ADHESIVES

CALL KS

DIRT

FPOXIES

"ICKY-PIC" CABLE GEL

INKS & DYES

0115

TAR





